



Halogen reflector

ELH 300W 120V 24PK

Philips' halogen reflector lamps offer the ideal no-fuss solution for a wide variety of medical, projection and scientific illumination systems. Their proven reliability makes them ideal for retrofit installations. The burners are precisely aligned for optimal light performance. Dichroic reflectors ensure heat dissipation towards the back of the optical system, which helps the optical system remain within temperature limits. A special blue-filter version blocking out unwanted light above 700 nm is available for dental curing applications. In addition, you get all the proven advantages of halogen technology such as a CRI of 100 – the same as natural sunlight for the best possible color rendering. Halogen lamps also create a comfortable warm white light, and they maintain their high lumen output with almost no lumen reduction throughout their lifetime.

Product data

General Information	
Base	GY5.3 [GY5.3]
Philips Code	13096
ANSI Code	ELH
LIF Code	-
Operating Position	Base Down +/- 90 D [Base Down +/- 90 D]
Main Application	Projection
Life to 50% Failures (Nom)	35 h
Light Technical	
Luminous Flux (Rated) (Nom)	850 lm
Correlated Color Temperature (Nom)	3350 K
Color Rendering Index (Nom)	100
Operating and Electrical	
Power (Rated) (Nom)	300 W

Voltage (Nom)	120 V
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Material	Quartz-UV Open
Reflector Finish	Facetted
Filament Dimensions WxH	-
Luminaire Design Requirements	
Bulb Temperature (Max)	900 °C
Pinch Temperature (Max)	350 °C
Working Distance WD	152.4 mm


Halogen reflector

Product Data

Order product name	13096 ELH 300W GY5.3 120V 1CT/24
EAN/UPC - Product	8711500410573
Order code	316190
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	24
Material Nr. (12NC)	923920936394
Net Weight (Piece)	0.026 kg

Dimensional drawing



13096 ELH 300W GY5.3 120V

Product	D (max)	C (max)
13096 ELH 300W GY5.3 120V 1CT/24	50.7 mm	44.5 mm

