



# **LED PAR30 S/L**

## 12PAR30L/EXPERTCOLOR/F40/940/DIM

Philips LED spots with a single optic beam, provide a clean beam that's free from shadows with beam angles from 15 and 40 degrees to suit every general lighting application.

#### **Product data**

General Information	
Lighting Technology	LED
Switching Cycle	50,000
Nominal lifetime	40,000 hour(s)
Cap-Base	E26 [Single Contact Medium Screw]
Light Technical	
Color Code	940 [CCT of 4000K]
Beam Angle (Nom)	40 degree(s)
Luminous Flux	950 lumen
Luminous Intensity (Nom)	2,100 cd
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	75.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	95
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	60 Hz
Input Frequency	60 Hz
Power Consumption	12 W
Lamp Current (Nom)	120 mA
Wattage Equivalent	75 W

Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	120 V
Temperature	
T-Case Maximum (Nom)	85 ℃
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Clear
Bulb Material	Plastic
Bulb Material Bulb Shape	Plastic PAR30L [PAR 3.75 inch/95mm Long]
Bulb Shape	
Bulb Shape  Approval and Application	PAR30L [PAR 3.75 inch/95mm Long]
Approval and Application Suitable For Accent Lighting	PAR30L [PAR 3.75 inch/95mm Long]  Yes
Approval and Application Suitable For Accent Lighting Energy Consumption kWh/1000 h	PAR30L [PAR 3.75 inch/95mm Long]  Yes - kWh
Approval and Application Suitable For Accent Lighting Energy Consumption kWh/1000 h Energy Certifications	PAR30L [PAR 3.75 inch/95mm Long]  Yes - kWh Energy Star
Approval and Application Suitable For Accent Lighting Energy Consumption kWh/1000 h Energy Certifications	PAR30L [PAR 3.75 inch/95mm Long]  Yes - kWh Energy Star


Datasheet, 2023, April 14 data subject to change

### LED PAR30 S/L

Order code	470988
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material number (12NC)	929001341204


Full product name	12PAR30L/EXPERTCOLOR/F40/940/DIM
EAN/UPC - Case	50046677470987

#### Dimensional drawing




Product	D	С
12PAR30L/EXPERTCOLOR/F40/940/DIM	94.8 mm	116.1 mm


#### Photometric data








#### Accent Lighting Spots - 12PAR30L/EXPERTCOLOR/F40/940/DIM




Light Distribution Diagram - 12PAR30L/EXPERTCOLOR/F40/940/DIM

#### LED PAR30 S/L

#### Lifetime





Life Expectancy Diagram - 12PAR30L/EXPERTCOLOR/F40/940/DIM

Lumen Maintenance Diagram - 12PAR30L/EXPERTCOLOR/F40/940/DIM

