


Lampes Incandescentes



BR30



G16.5



G25



R16



R20

Code de commande	Description	Watts (W)	Culot	Volts (VCA)	Finition	Filament	Vie L70 (h)	Flux lumineux (lm)	HCL (po)	HCL (mm)	Qté caisse (int./ext.)
BR30											
52452	65BR30/FL/5M/ES/130V/ELUME 2P	65	E26	130	Givrée	CC-6	5 000	590	4	101	12/60
G16.5											
52453	25G16.5/CL/3M/E12/130V/ELUME 2P	25	E12	130	Claire	C-7A	3 000	160	1 7/8	48	24/120
52454	40G16.5/CL/3M/E12/130V/ELUME 2P	40	E12	130	Claire	C-7A	3 000	315	1 7/8	48	24/120
G25											
52455	40G25/CL/3M/130V/ELUME 2P	40	E26	130	Claire	C-9	3 000	350	2 7/8	73	12/60
52457	40G25/WH/3M/130V/ELUME 2P	40	E26	130	Blanc	C-9	3 000	330	2 7/8	73	12/60
R16											
52459	40R16/SW/1M/120V/ELUME 2P	40	E26	120	Blanc doux	CC-6	1 000	445	3 1/32	77	12/60
52460	60R16/SW/1M/130V/ELUME 2P	60	E26	130	Blanc doux	CC-6	1 000	730	3 1/32	77	12/60
R20											
52462	30R20/FL/5M/130V/ELUME 2P	30	E26	130	Givrée	C-9	5 000	135	2 9/16	65	12/60
61707	45R20/FL/5M/130V/ELUME 2P	45	E26	130	Givrée	CC-6	5 000	242	2 9/16	65	12/60
52463 ¹	75R20/FL/5M/130V/ELUME 2P	75	E26	130	Givrée	C-9/5	5 000	540	2 9/16	65	12/60

¹ Cet item n'est plus produit conformément à la loi sur les standards en matière d'efficacité énergétique, il sera disponible jusqu'à épuisement des stocks.