



5262

15 Amp Duplex Receptacle/Outlet, Industrial Grade, Self-Grounding

Duplex Receptacle Outlet, Extra Heavy-Duty Industrial Specification Grade, Smooth Face, 15 Amp, 125 Volt, Back or Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - Brown

ROHS Compliant : Yes

Technical Information

AC Horsepower Ratings

At Rated Voltage : 1/2 HP

Electrical Specifications

Amperage : 15 A

Current Limiting : Full Rated Current

Dielectric Voltage :
Withstands 2000V per UL498

Grounding : Self-Grounding

Pole : 2

Temperature Rise : Max 30C
after 250 cycles OL at 200
percent rated current

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-2 per
UL 94

Operating Temperature : -40°
C to 60°C

Material Specifications

Body Material : Thermoplastic
Nylon

Clamp Nuts : Zinc-Plated Steel

Color : Brown

Face Material : Thermoplastic
Nylon

Ground Clips : Brass-Plated

Grounding Screw : Brass 8-32

Line Contacts : Brass Triple-
Wipe

Strap Material : Brass

Terminal Screws : Brass 10-32

Yoke : Brass

Mechanical Specifications

Product ID : Ratings are
permanently marked on device

Screw Terminal Torque : 14-
18 in-lbs

Product Features

Color : Brown

Device Type : Duplex
Receptacle Outlet

Color :  Brown

UPC Code : 078477139417

Country Of Origin : Please Contact
Customer Service

NEMA :  5-15R

Available Colors :



Black



Red



Gray



White




Ivory

Terminal Accom. : 14-10 AWG **Grade** : Extra Heavy-Duty
Industrial Specification Grade
Terminal ID : Brass-Hot,
Green-Ground, Silver-Neutral **NEMA** : 5-15R
Termination : Back or Side
Wire
Torque Range : 14-16 in-lbs

Standards and Certifications

ANSI : C-73
CSA C22.2 No. 42 : File
152105
NOM : 057
UL Fed Spec WC-596 : File
E13399
UL498 : File E13399
Warranty : 10-Year Limited

Wiring Diagram



SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS:
JOB NUMBER: 	

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.