

Incandescent Lamps

Order code	Description	Watts (W)	Base	Volts (V)	Lumens at 120 V (lm)	Average life (hrs)	Filament type	Finish	Case qty (inner/master)
CA4.5									
MOL : 2 3/4 in. (70 mm) LCL : 1 5/8 in. (41 mm)									
52153	10CA4.5/CL/2M/E12/130V/STD	10	E12	130	40	2 000	C-7A	Clear	6/120
CA8									
MOL : 3 19/32 in. (91 mm) LCL : 1 25/32 in. (45 mm)									
52157	10CA8/F/2.5M/E12/130V/STD	10	E12	130	50	2 500	C-7A	Frost	25/500
50641	15CA8/CL/2.5M/E12/130V/STD	15	E12	130	70	2 500	C-7A	Clear	6/120
10269	15CA8/F/2.5M/E12/130V/STD	15	E12	130	70	2 500	C-7A	Frost	25/500
50643	25CA8/F/2.5M/E12/130V/STD	25	E12	130	115	2 500	C-7A	Frost	6/120
50642	40CA8/CL/2.5M/E12/130V/STD	40	E12	130	215	2 500	C-7A	Clear	25/500
50644	40CA8/F/2.5M/E12/130V/STD	40	E12	130	215	2 500	C-7A	Frost	25/500
CA10									
MOL : 3 29/32 in. (99 mm) LCL : 2 1/8 in. (54 mm)									
51051	25CA10/CL/3M/130V/STD	25	E26	130	120	3 000	C-7A	Clear	6/120
50629	25CA10/F/3M/130V/STD	25	E26	130	115	3 000	C-7A	Frost	6/120
MOL : 4 3/32 in. (104 mm) LCL : 1 7/8 in. (48 mm)									
50615	25CA10/CL/3M/E12/130V/STD	25	E12	130	135	3 000	CC-2V	Clear	6/120
50618	25CA10/F/3M/E12/130V/STD	25	E12	130	115	3 000	CC-2V	Frost	6/120
50616	40CA10/CL/3M/E12/130V/STD	40	E12	130	235	3 000	CC-2V	Clear	6/120
50619	40CA10/F/3M/E12/130V/STD	40	E12	130	205	3 000	CC-2V	Frost	6/120
50617	60CA10/CL/3M/E12/130V/STD	60	E12	130	455	3 000	CC-2V	Clear	6/120
50620	60CA10/F/3M/E12/130V/STD	60	E12	130	450	3 000	CC-2V	Frost	6/120
F15									
MOL : 4 1/2 in. (115 mm) LCL : 2 9/16 in. (65 mm)									
50751	25F15/CL/2M/130V/STD	25	E26	130	160	2 000	CC-6	Clear	25/100
50750	40F15/CL/2M/130V/STD	40	E26	130	305	2 000	CC-6	Clear	25/100
G9.5									
MOL : 2 1/16 in. (52 mm) LCL : 1 1/2 in. (38 mm)									
52165	7.5G9.5/CL/1M/E12/130V/STD	7	E12	130	40	1 000	C-7A	Clear	25/500
G11									
MOL : 2 5/16 in. (59 mm) LCL : 1 5/8 in. (41 mm)									
69785	7.5G11/CL/1M/E12/130V/STD S2	7.5	E12	130	40	1 000	C-7A/3	Clear	6/120
69787	7.5G11/CL/1M/130V/STD S2	7.5	E26	130	40	1 000	C-7A/3	Clear	6/120
G13									
MOL : 2 3/8 in. (60.5 mm) LCL : 1 11/16 in. (43 mm)									
50681	10G13/CL/3M/E12/130V/STD	10	E12	130	50	3 000	C-7A	Clear	25/500
50682	25G13/CL/3M/E12/130V/STD	25	E12	130	135	3 000	CC-2V	Clear	6/120
G16.5									
MOL : 3 in. (76 mm) LCL : 1 7/8 in. (48 mm)									
10334	5G16.5/CL/3M/E12/130V/STD	5	E12	130	20	3 000	C-7A	Clear	6/120
10268	10G16.5/CL/3M/E12/130V/STD	10	E12	130	50	3 000	C-7A	Clear	6/120
50660	15G16.5/CL/3M/E12/130V/STD	15	E12	130	70	3 000	C-7A	Clear	6/120
50662	15G16.5/WH/3M/E12/130V/STD	15	E12	130	60	3 000	C-7A	White	6/120
50652	25G16.5/WH/3M/E12/130V/STD	25	E12	130	120	3 000	CC-2V	White	6/120
52453	25G16.5/CL/3M/E12/130V/ELUME 2P	25	E12	130	160	3 000	C-7A	Clear	24/120
50777	25G16.5/CL/3M/E14/130V/STD	25	E14	130	160	3 000	CC-6	Clear	6/120
50649	25G16.5/CL/3M/130V/STD	25	E26	130	135	3 000	CC-2V	Clear	6/120
50653	25G16.5/WH/3M/130V/STD	25	E26	130	120	3 000	CC-2V	White	6/120
50654	40G16.5/WH/3M/E12/130V/STD	40	E12	130	230	3 000	CC-2V	White	6/120
52454	40G16.5/CL/3M/E12/130V/ELUME 2P	40	E12	130	160	3 000	C-7A	Clear	24/120
50651	40G16.5/CL/3M/130V/STD	40	E26	130	250	3 000	CC-2V	Clear	6/120
50655	40G16.5/WH/3M/130V/STD	40	E26	130	230	3 000	CC-2V	White	6/120
50656	60G16.5/CL/3M/E12/130V/STD	60	E12	130	440	3 000	CC-2V	Clear	6/120
50658	60G16.5/WH/3M/E12/130V/STD	60	E12	130	400	3 000	CC-2V	White	6/120