

Toggle Switches

MEDIUM-DUTY TOGGLE SWITCHES (WEATHER-RESISTANT)

Standard 11/16" 'Bat' Handle. Mounting stem: 15/32". Rating 20A @ 12VDC



765010



765018

Feature	Benefit
O-Ring Seal + Plastic Coating	Weatherproofs the switch
ON/OFF Face Plate	Easily identifies the current function of switch
Wire Leads – Tin Plated Copper (14GA, 8" Long)	Tin Plating on the copper prolongs life of switch

Type	Description	1 PC/PK	25 PCS/PK
2 Position (ON-OFF)	SPST	765010	765010B
3 Position (Mom ON-OFF-Mom ON)	SPDT	765018	765018B



765075



765073



LIGHT-DUTY TOGGLE SWITCHES

The best combination of space-saving size and economy for universal, lighter duty applications. CUL approval, where shown. Each switch comes with a Face Plate imprinted with an ON-OFF Face Plate.

S.P.S.T. (SINGLE POLE – SINGLE THROW)

Positions	Circuitry	Terminal Type	Amp Rating	Handle Length/ Type	Mounting Stem Diameter	1 PC/PK	25 PCS/PK
2	ON-OFF	2 Screws	35A @ 6VDC 20A @ 12VDC	Chrome, 'Bat'-style handle - 11/16" Long	7/16" Dia.	765075	765075B
2	ON-OFF	2 Blades	6A @ 125VAC 3A @ 250VAC	Chrome, 'Bat'-style handle - 16mm Long	15/32" Dia.	765072	765072B
2	ON-OFF	2 Wires	6A @ 125VAC 3A @ 250VAC	Chrome, 'Bat'-style handle - 16mm Long	15/32" Dia.	765073	765073B
2	ON-OFF	2 Wires	6A @ 125VAC 3A @ 250VAC	Chrome, 'Ball'-tip handle - 11mm Long	15/32" Dia.	*765077	*765077B *NEW



765072



*765077

