

Technical Information Bulletin

DESIGN LED Lamps



Date: _____ Name of distributor: _____
 In hands date of project: _____ Client #: _____
 Project name/Number: _____ Name of end user: _____

ORDERING INFORMATION

Order code: 67608
Description: P20/7W/40K/45/DESIGN/STD
UPC: 69549676084
Case quantity: 10/60



MOL: 3 11/32" (85 mm) Dia.: 2 15/32" (63 mm)

PHYSICAL DATA

Type: PAR20
Base: E26
Material: Glass
Lens type: Clear

PERFORMANCE DATA

Watts (W): 7
Lamp volts (VAC): 120
Colour temperature (K)¹: 3 000
Life L70 (hrs): 25 000
Lumens (lm)²: 500
Lumens per watt (lm/W): 71
Traditional equivalent (W): 50
CRI: 80
Beam angle (°): 45
CBCP (cd): 520
THD (%): 55
Frequency (Hz): 60
Power factor: 0.88
Operating temperature range: -20°C to 45°C (-4°F to 113°F)

¹ Typical colour temperature range: +/- 5 %
² Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %

COMPATIBLE DIMMERS

Legrand	RH703PTUTC
Cooper	SLC03P
Leviton	6615, IPL06, 6674, DSL06-1LZ, IPE04-1LZ, DDMX1
Lutron	PD-6WCL,RRD-6NA, DVCL-153P, CTCL-153P, DVCL-253P, AYCL-253P, DVRP-253P, SELV-300P, MACL-153P,



Qty	Description	Price

I accept the specifications of the luminaire configuration mentioned above.

Name: _____
 Company: _____
 Signature: _____ Date: _____

This lighting equipment complies with Canadian standard ICES-005 for use in residential applications. Data is based upon tests performed in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.