



# CFL

CFL lamps provide the same amount of light (lumens) as regular incandescent lamps, but have a lower wattage rating. As a result, they consume less energy and cause less pollution. ALL STANDARD CFL lamps meet NEMA voluntary commitment on mercury content in CFL lamps and are all cULus listed, where applicable.

## Specialty



20 W; MOL: 5 1/8 in. (130 mm)  
Ø 2 9/32 in. (68 mm)

High Power  
Factor



MOL: 5 1/16 in. (154 mm)  
Ø 2 1/4 in. (57 mm)

Trilight

Order code	Description	Watts (W)	Base	Color temp. (K)	Lumen output (lm)	Average life (hrs)	CRI	Incandescent equivalent (W)	Case qty (inner/master)
<b>High Power Factor</b>									
58404	CF20/HPF/27K/SPIRAL/E26/STD	20	E26	2 700	1 200	10 000	82	75	12/48
<b>Trilight</b>									
58959	CF13/20/25/27K/SPIRAL/E26/STD	13 20 25	E26	2 700	900 1 200 1 550	8 000	80	60 75 100	6/48



# T2 Spiral



MOL: 3 13/16 in. (97 mm)

7 W



MOL: 3 31/32 in. (101 mm)

9 W



MOL: 4 1/8 in. (105 mm)

13 W



MOL: 4 11/32 in. (110 mm)

18 W



MOL: 4 7/8 in. (124 mm)

23 W



MOL: 5 1/16 in. (129 mm)

26 W

Order code	Description	Watts (W)	Base	Color temp. (K)	Lumen output (lm)	Average life (hrs)	CRI	Incandescent equivalent (W)	Case qty (inner/master)
<b>7 watts</b>									
62764	CF7/T2/27K/SPIRAL/E26/ELUME	7	E26	2 700	430	10 000	82	40	6/48
<b>9 watts</b>									
61020	CF9/T2/27K/SPIRAL/E26/ELUME	9	E26	2 700	550	10 000	82	40	6/48
62311	CF9/T2/41K/SPIRAL/E26/ELUME	9	E26	4 100	550	10 000	82	40	6/48
<b>13 watts</b>									
61021	CF13/T2/27K/SPIRAL/E26/ELUME	13	E26	2 700	900	10 000	82	60	6/48
61024	CF13/T2/30K/SPIRAL/E26/ELUME	13	E26	3 000	900	10 000	82	60	6/48
61026	CF13/T2/35K/SPIRAL/E26/ELUME	13	E26	3 500	850	10 000	82	60	6/48
<b>18 watts</b>									
62832 <sup>1</sup>	CF18/T2/27K/SPIRAL/E26/STD	18	E26	2 700	1 250	12 000	82	75	6/48
62834 <sup>1</sup>	CF18/T2/35K/SPIRAL/E26/STD	18	E26	3 500	1 250	12 000	82	75	6/48
<b>23 watts</b>									
61032	CF23/T2/27K/SPIRAL/E26/ELUME	23	E26	2 700	1 600	10 000	82	100	6/48
61033	CF23/T2/30K/SPIRAL/E26/ELUME	23	E26	3 000	1 600	10 000	82	100	6/48
61034	CF23/T2/41K/SPIRAL/E26/ELUME	23	E26	4 100	1 600	10 000	82	100	6/48
61035	CF23/T2/50K/SPIRAL/E26/ELUME	23	E26	5 000	1 600	10 000	82	100	6/48
<b>26 watts</b>									
63389 <sup>1</sup>	CF26/T2/30K/SPIRAL/E26/STD	26	E26	3 000	1 750	10 000	82	100	6/48
<b>T2 Spirals packs</b>									
61022	CF13/T2/27K/SPIRAL/E26/ELUME 4P	13	E26	2 700	900	10 000	82	60	1/64
61025	CF13/T2/30K/SPIRAL/E26/ELUME 4P	13	E26	3 000	900	10 000	82	60	1/64
61027	CF13/T2/41K/SPIRAL/E26/ELUME 4P	13	E26	4 100	880	10 000	82	60	1/64
61023	CF13/T2/27K/SPIRAL/E26/ELUME 12P	13	E26	2 700	900	10 000	82	60	1/48



# GU24 Based



13 W: MOL: 3.5/8 in. (92 mm)  
 Ø 1.13/16 in. (46 mm)  
 18 W: MOL: 4.13/32 in. (112 mm)  
 Ø 1.1/8 in. (54 mm)  
 23 W: MOL: 4.13/32 in. (112 mm)  
 Ø 1.1/8 in. (54 mm)

**Spiral (GU24)**



23 W: MOL: 4.27/32 in. (123 mm)  
 Ø 2.1/8 in. (54 mm)

**Dimmable Spiral (GU24)**

Order code	Description	Watts (W)	Base	Color temp. (K)	Lumen output (lm)	Average life (hrs)	CRI	Incandescent equivalent (W)	Case qty (inner/master)
<b>Spiral</b>									
61843	CF13/T2/35K/SPIRAL/GU24/STD	13	GU24	3 500	880	10 000	82	60	6/48
61846	CF23/T2/27K/SPIRAL/GU24/STD	23	GU24	2 700	1 600	10 000	82	100	6/48
61847	CF23/T2/41K/SPIRAL/GU24/STD	23	GU24	4 100	1 600	10 000	82	100	6/48
<b>Spiral - Dimmable</b>									
60921 <sup>1</sup>	CF23/D/27K/SPIRAL/GU24/STD	23	GU24	2 700	1 500	10 000	82	100	6/48

# High Wattage Spiral



MOL: 6.3/32 in. (155 mm)  
 Ø 2.5/8 in. (67 mm)

**32 W**



MOL: 7.9/32 in. (195 mm)  
 Ø 2.5/8 in. (67 mm)

**40 W**



MOL: 9.21/32 in. (245 mm)  
 Ø 3.5/32 in. (80 mm)

**55 W**



MOL: 9.7/16 in. (240 mm)  
 Ø 3.17/32 in. (80 mm)

**65 W**



MOL: 9.31/32 in. (253 mm)  
 Ø 4.1/32 in. (102 mm)

**85 W**

Order code	Description	Watts (W)	Base	Color temp. (K)	Lumen output (lm)	Average life (hrs)	CRI	Incandescent equivalent (W)	Case qty (inner/master)
<b>32 watts</b>									
60932	CF32/27K/SPIRAL/E26/STD	32	E26	2 700	2 000	10 000	82	120	6/48
58412	CF32/65K/SPIRAL/E26/STD	32	E26	6 500	2 100	10 000	82	120	6/48
<b>40 watts</b>									
60940	CF40/35K/SPIRAL/E26/STD	40	E26	3 500	2 600	10 000	82	150	6/48
60942	CF40/50K/SPIRAL/E26/STD	40	E26	5 000	2 600	10 000	82	150	6/48
<b>55 watts</b>									
60922	CFL55/27K/SPIRAL/E26/STD	55	E26	2 700	3 700	10 000	82	300	6/48
<b>65 watts</b>									
60925	CFL65/50K/SPIRAL/E26/STD	65	E26	5 000	4 300	10 000	82	300	6/48
<b>85 watts</b>									
60926	CFL85/27K/SPIRAL/E26/STD	85	E26	2 700	5 400	10 000	82	350	6/12

