

Date: \_\_\_\_\_  
 In hands date of project: \_\_\_\_\_  
 Project name/Number: \_\_\_\_\_  
 Name of distributor: \_\_\_\_\_  
 Client #: \_\_\_\_\_  
 Name of end user: \_\_\_\_\_



Nominal length : 46 in. (1 168 mm) Dia. : 1/8 in. (16 mm)

### ORDERING INFORMATION

Order code: 65482  
 Description: LED/T5/S2/25.5W/865/46/STD/SMX  
 UPC: 69549654822  
 Case quantity: 25



### PERFORMANCE DATA

Shape: T5  
 Base: G5  
 Watts (W): 25.5  
 Starting method: Program Start  
 Lamp voltage (VAC): 120 V-277 V / 347 V  
 Color temperature (K)\*\*: 6 500  
 Average life (L70 hours): 50 000  
 Initial Lumens (lm)\*: 3 200  
 Initial lumens per watt (lm/W): 125  
 CRI: >80  
 Beam angle (°): >240  
 Coating: PET Polyethylene Terephthalate  
 Operating temperature range: -20°C / -4°F to 45°C / 113°F

\*Initial lumens range: +/- 10 %

\*\*Typical colour temperature range: +/- 5 %



Intertek  
 CONFORMS TO NSF/ANSI 2

Please refer to the ballast compatibility list to confirm lamp compatibility with the existing luminaire.

### CAUTIONS

THIS LAMP OPERATES ON PROGRAM START ELECTRONIC BALLASTS. Direct replacement for 54 watts T5 lamps only. Risk of fire. Do not install this lamp in a pre-heat luminaire. Risk of electric shock – for use in damp locations. This device is not intended for use with emergency exit fixtures or emergency exit lights. Not for use in totally enclosed luminaires.

Qty	Description	Price

I accept the specifications of the lamp configuration mentioned above.

Name: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Signature: \_\_\_\_\_

Date: \_\_\_\_\_

Data is based upon tests performed in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

September 2, 2015

**STANDARD**™