

QUICK DISCONNECTS




FEMALE

				
Wire Range	Tab Size	Non-insulated	P.V.C.	Nylon
22-18	.110X.020	FR1A 110	FR4A 110	FR6A 110
	.187X.020	FR1A 187	FR4A 187	FR6A 187
	.250X.032	FR1A 250	FR4A 250	FR6A 250
16-14	.110X.020	FR1B 110	FR4B 110	FR6B 110
	.187X.020	FR1B 187	FR4B 187	FR6B 187
	.250X.032	FR1B 250	FR4B 250	FR6B 250
12-10	.250X.032	FR1C 250	FR4C 250	FR6C 250

FEATURES: The tin plated brass connector features the rolled edge design for maximum spring-like insertion/withdrawal force. Protruding lip and beveled floor with detent aid in insertion and retention of tab and a wire stop prevents over-insertion of stripped wire. Other sizes and styles available. Check with factory for .187 x .032 size parts.

MALE

				
Wire Range	Tab Size	Non-insulated	P.V.C.	Nylon
22-18	.187X.020	MT1A 187	MT4A 187	MT6A 187
	.250X.032	MT1A 250	MT4A 250	MT6A 250
16-14	.187X.020	MT1B 187	MT4B 187	MT6B 187
	.250X.032	MT1B 250	MT4B 250	MT6B 250
12-10	.250X.032	MT1C 250	MT4C 250	MT6C 250

FEATURES: Pure copper tab plated with zinc chromate for maximum insertion/withdrawal values affording greater corrosion resistance. Lip for easier insertion. NOTE: Consult factory for .187 x .032 size parts.

Add suffix "M" for 1000 pack


Add suffix "P" for Pro Pack (Quantities vary by Part #)

P.V.C. & Nylon disconnects rated -55°C to 105°C

Approved installation tool: See tool chart pages E-2,3,4

Economy installation tools: 453, HTS1000, RAT-NINS, RAT-DISC (insulated)

DUAL ADAPTERS




Part Number **MMFA** Converts one .250 x .032" male tab to two male tabs. Dual Male-Female Adapter.



Copper Stranded Wire Only
(All items listed on this page)

FLAG DISCONNECTS



Wire Range	Tab Size	Non-insulated
22-18	.187X.020	FLFR1A 187†
	.250X.032	FLFR1A 250†
16-14	.187X.020	FLFR1B 187†
	.250X.032	FLFR1B 250†
12-10	.250X.032	FLFR1C 250*††

Add suffix "M" for 1000 pack

Add suffix "P" for Pro Pack
(Quantities vary by Part #)

†Approved installation tool:


See tool chart pages E-2,3,4

††Economy installation tool: HTS2000

* Not CSA or UL Listed

RECEPTACLES

INSULATED TAB RECEPTACLE



Part No. **MDT250** For connecting two .250 x .032 Female Quick Disconnects

