

Constant Current - 0~10V Dimming									
Output Power	Model	Output Voltage	Output Current	Input Voltage	Efficiency	PF	THD	Dimension (mm)	IP
125W	**PDA125W-1A4F-R	67~89V	1400mA	108~305V	>90%	≥0.9	<20%	217.2x68x38	IP65
125W	**PDA125W-3A1F-R	30~40.3V	3100mA	108~305V	>89%	≥0.9	<20%	217.2x68x38	IP65
150W	**PDA150W-S350G-R	0~428V	350mA	108~305V	>90%	≥0.9	<20%	241x59x39.1	IP66
150W	**PDA150W-S530G-R	0~283V	530mA	108~305V	>92%	≥0.9	<20%	241x59x39.1	IP66
150W	**PDA150W-S700G-R	0~210V	700mA	108~305V	>92%	≥0.9	<20%	241x59x39.1	IP66
150W	**PDA150W-S1A0G-R	0~143V	1050mA	108~305V	>92%	≥0.9	<20%	241x59x39.1	IP66
150W	**PDA150W-S1A5G-R	0~100V	1500mA	108~305V	>92%	≥0.9	<20%	241x59x39.1	IP66
150W	**PDA150W-S1A7G-R	0~89V	1680mA	108~305V	>92%	≥0.9	<20%	241x59x39.1	IP66

Constant Current - AC Bi-level Dimming									
48W	**PDA048K-350G-R	27~34V	350mA/4ch	108~305V	>84%	≥0.9	<20%	242x43.5x30.5	IP65
48W	**PDA048K-450G-R	21~26.5V	450mA/4ch	108~305V	>84%	≥0.9	<20%	242x43.5x30.5	IP65

Constant Current - PWM Dimming									
30W	*PDM030V-700C-H	12~42V	700mA/2ch	90~264V	>80%	≥0.9	<20%	149.3x46x24	IP20

Constant Current - Trailing Edge Dimming									
10W	*PDM010G-700C-R	7.5~12V	700mA	185~264V	>70%	≥0.92	<20%	106x40x21	IP20
10W	*PDM010H-700C-R	7.5~12V	700mA	90~132V	>70%	≥0.7	<20%	106x40x21	IP20
30W	*PDM030G-700C-H	15~42V	700mA	185~264V	>80%	≥0.95	<20%	132x40x21	IP20
30W	*PDM030H-700C-H	15~42V	700mA	90~132V	>80%	≥0.9	<20%	132x40x21	IP20

Constant Current - Triac Dimming									
Output Power	Model	Output Voltage	Output Current	Input Voltage	Efficiency	PF	THD	Dimension (mm)	IP
10W	PDA010N-350B-R	21~30V	350mA	90~132V	>78%	≥0.9	<20%	79.8x70.1x25.4	IP67
10W	PDA010N-700B-R	9.8~14V	700mA	90~132V	>78%	≥0.9	<20%	79.8x70.1x25.4	IP67
10W	PDA010N-1A0B-R	7~10V	1000mA	90~132V	>78%	≥0.9	<20%	79.8x70.1x25.4	IP67
15W	PDA015N-350B-R	29.4~42V	350mA	90~132V	>81%	≥0.9	<20%	79.8x70.1x25.4	IP67
15W	PDA015N-700B-R	14.7~21V	700mA	90~132V	>81%	≥0.9	<20%	79.8x70.1x25.4	IP67
15W	PDA015N-1A0B-R	10.5~15V	1050mA	90~132V	>80%	≥0.9	<20%	79.8x70.1x25.4	IP67
25W	PDA025H-350A-H	45~72V	350mA	90~132V	>83%	≥0.9	<20%	78x50x25.2	IP66
25W	PDA025H-520A-H	30~48V	520mA	90~132V	>83%	≥0.9	<20%	78x50x25.2	IP66
25W	PDA025H-700A-H	24~36V	700mA	90~132V	>83%	≥0.9	<20%	78x50x25.2	IP66
25W	PDA025H-1A0A-H	16~24V	1050mA	90~132V	>83%	≥0.9	<20%	78x50x25.2	IP66

Constant Voltage - 0~10V Dimming									
72W	**PDA072W-24VG-R	24V	3000mA	108~305V	>87%	≥0.9	<20%	242x43.5x30.5	IP65
80W	**PDA080W-48VG-R	48V	1670mA	108~305V	>87%	≥0.9	<20%	242x43.5x30.5	IP65
125W	**PDA125W-24VF-R	24V	5200mA	108~305V	>86%	≥0.9	<20%	217.2x68x38	IP65
125W	**PDA125W-48VF-R	48V	2600mA	108~305V	>87%	≥0.9	<20%	217.2x68x38	IP65

* Please contact us for model availability details.

** Please inquire for 90~305V version.